



Knight

Parameter



R22

Model	Power supply	Function	Capacity (Btu/h)	Power input (W)	EER/C.O.P (W/W)	Indoor unit (W×H×D)				Airflow (m³/h)	Outdoor unit (W×H×D)				Loading quantity	
						Body size (mm)	Package size (mm)	N.W/G.W (kg)	Noise dB(A) (H/M/L)		Body size (mm)	Package size (mm)	N.W/G.W (kg)	Noise dB(A)	40' GP	40' HQ
GWCN24FAND1A1A	1Ph 220V 60Hz	Cooling	24000	2700	2.61	1178 × 326 × 227	1265 × 417 × 333	17.5/24	49/47/43	1100	1018 × 700 × 412	1100 × 755 × 450	55/60	55	102	117
GWHN24FAND1A1A		Cooling	24000	2700	2.61				48/47/43					58		
		Heating	26000	2600	2.93											
GWCN28FAND1A1A		Cooling	28000	3200	2.50	1178 × 326 × 227	1265 × 417 × 333	17.5/24	49/47/45	1100	1018 × 840 × 412	1100 × 880 × 450	90/105	60	76	92
GWHN28FAND1A1A		Cooling	28000	3200	2.56											
		Heating	30000	3200	2.75											

Note: For technical improvement, the specifications, designs and information in this catalogue are subject to change without notice.

The specifications, designs and information on this website are subject to change without notice; and specifications may be different between different markets, please consult your local dealer/distributor for details.